



AIR Flexible-21/15

AIR Flexible-21/15

- > Simple - Only Need 3 Images for Training
- > High-Speed - Recognize in 1 Second
- > Easy - Integration with existing PoS
- > Affordable - No need Internet
- > Built-in LED Light Bar
- > Come with RENITY AIR (AI Object Recognition) software

+ Spec

-Front I/O-	
USB Port	4 x USB 3.0
Panel	
LCD Size	21.5" 15.6"
Display Type	FHD
Resolution	1366 x 768
Pixel pitch	0.252mm(H) x 0.252mm(V)
Luminance	300 cd/m ²
Contrast ratio	500
Viewing angle	80 (U), 80 (D), 80 (L), 80 (R)
Response time	8 ms
Backlight	LED
Touch Type	PCAP Multi-Touch support up to 10 points
Touch Light Transmission	88 %
Data Collection	
Camera	FHD
Power Requirement	
DC Input	+12V ~ +26V
DC Input Connector	Lockable DC Jack
Adapter	Input: 100 ~ 240Vac/ 50 ~ 60Hz Output: 60W Adapter (12V @ 5A Adapter) AC-DC Adapter
Mechanical & Environmental	
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F)
Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)
Operating Humidity	40°C @ 95% Relative Humidity, Non-condensing