



BAX-R4U0

4U Rackmount Chassis

- > 4U Rackmount
- > Up to 12"(W) x 9.6"(D) ATX compliant MB
- > 3 x 3.5" Internal Drive Bay
- > 2 x 3.5" + 3 x 5.25" External Drive Bay
- > 7 x Full Height expansion slots
- > 500W PS2 100-240Vac Power Supply
- > Dimension 515 x 430 x 174.8 mm
- > Net weight: 12.09kg(Chassis only)

+ Spec

-System Information-	
Processor	Depend on MB
Platform Controller Hub	Depend on MB
Watchdog Timer	H/W Reset, 1sec. ~ 65535sec./min. 1sec. or 1min. step
H/W Status Monitor	CPU temperature monitoring Voltages monitoring CPU fan speed control
TPM	Onboard Infineon SLB9665 support TPM 2.0
SBC	ATX MB
-Front I/O-	
USB Port	2 x USB 2.0
Power Button	System power on/off
Reset Button	System reset
LED Indicator	Power status, HDD, LAN activity LEDs
Expansion	
Expansion	7 x Full Height expansion slots on chassis
Storage	
Storage	3 x 3.5" Internal Drive Bay 2 x 3.5" + 3 x 5.25" External Drive Bay
Power Requirement	
Adapter	500W PS2 100-240Vac Power Supply
Mechanical & Environmental	
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Storage Temperature	-30°C ~ 70°C (-22°F ~ 158°F)
Operating Humidity	0% ~ 90% Relative Humidity, Non-condensing
Dimension (W x L x H)	515 x 430 x 174.8 mm
Construction	Metal
Ordering Information	
Ordering Information	BCC-CASE-R4U0-02R 4U Rackmount Chassis(without 500W PSU) ACC-PSU-500N-01R Power Supply ATX 500W