



## EMS-SKLU

### 6th Gen Intel®Core™ Processor i7/i5/i3/Celeron Fanless Rugged Embedded System

- > Onboard 6th Gen Intel® Core™ SoC i7/i5/i3/Celeron BGA Processor
- > One 260-pin SODIMM Socket Up to 16GB DDR4 2133MHz SDRAM
- > 1xDP,2xLAN,1xCOM1,4xUSB 3.0,1xMulti-Function Port (1xGPIO,1xCOM2,1xAudio,1xSMBus,2xPS2)
- > Expansion Slot Supports 1 Mini PCIe Slot, 1 M.2, 1 IET Interface
- > Front Access Swappable 2.5" Drive Bay, 2 SIM Card
- > Rugged Design for Vibration & Shock Protection
- > Fanless Operating from -20 ~ 60°C, Support IP50
- > Power Input: Typical 12/24 Vdc ( +9~ 32V )
- > Supports Intel® iAMT 11.0, TPM2.0 , Turbo Boost Technology, vPro, Wake on LAN, RAID 0/1
- > Service Window, Easy to Install M.2, Memory and Mini PCIe Module

#### + Spec

-System Information-	
<b>Processor</b>	6th Gen Intel® Core™ i7-6600U, 2-Core, 2.6GHz processor 6th Gen Intel® Core™ i5-6300U, 2-Core, 2.4GHz processor 6th Gen Intel® Core™ i3-6100U, 2-Core, 2.3GHz processor 6th Gen Intel® Celeron® 3955U, 2-Core, 2.0GHz processor
<b>System Memory</b>	1 x 16GB DDR4 SDRAM
<b>Watchdog Timer</b>	H/W Reset, 1sec. ~ 65535sec.
<b>H/W Status Monitor</b>	Monitoring CPU & System Temperature and Voltage
<b>SBC</b>	EBM-SKLUS
Expansion	
<b>Expansion</b>	1 x Avalue 80-Pin IET Interface 1 x Mini PCIe, supports PCIe1/USB2.0 1 x M.2 (2242/3042) B-Key, supports SATA/ PCIe1/ USB3.0
Storage	
<b>Storage</b>	1 x 2.5" Drive Bay 1 x M.2 (SATA)
I/O	
<b>USB Port</b>	4 x USB 3.0
<b>COM Port</b>	2 x RS-232/422/485 (Jumper), supports auto-flow
<b>GPIO</b>	1 x 12bit GPIO
<b>Other</b>	2 x SIM Card Slot 1 x SMBus 2 x PS2/ KB & MS 2 x Knockouts for Antenna Mounting
Display	
<b>Graphic Chipset</b>	Intel® Skylake SoC integrated Graphics
<b>Spec. &amp; Resolution</b>	DP: Max. resolution 4096x2304 @ 60Hz
Audio	
<b>Audio Codec</b>	Realtek ALC888S supports 2.1-CH
<b>Audio Interface</b>	Mic-In, Line-In and Line-Out
Ethernet	
<b>LAN Chipset</b>	1 x Intel® I211AT 1 x Intel® I219LM
<b>Ethernet Interface</b>	10/100/1000 Base-Tx GbE compatible
<b>LAN Port</b>	2 x RJ-45
Power Requirement	
<b>DC Input</b>	Power input: Typical 12/24Vdc(+9V ~ +32V) TVS component for surge protection Reverse current/voltage protection
<b>DC Input Connector</b>	3-Pin Terminal Block
<b>ACPI</b>	Single Power ATX Support S0, S3, S4, S5 ACPI5.0 Compliant
<b>Power Mode</b>	AT/ATX (ATX is default setting)
<b>Adapter</b>	Optional AC-DC Adapter
Mechanical & Environmental	
<b>Operating Temperature</b>	(w/SSD), ambient w/ air flow -20°C ~ 60°C (-4°F ~ 140°F)
<b>Storage Temperature</b>	-30°C ~ 70°C (-22°F ~ 158°F)
<b>Operating Humidity</b>	40°C @ 95% Relative Humidity, Non-condensing
<b>Dimension (W x L x H)</b>	9.45" x 5.96" x 1.77" (240mm x 151.5mm x 45mm)



<b>Weight</b>	1.5kg (system) 2.4kg (w/ package)
<b>Vibration Test</b>	With SSD : 5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 1hr/axis
<b>Shock Test</b>	With SSD : 50Grms, IEC 60068-2-27, Half Sine, 11ms
<b>Mounting Kit</b>	Wall Mount kit (Standard)
<b>Construction</b>	Aluminum + Metal
<b>Ordering Information</b>	
<b>Ordering Information</b>	<p>EMS-SKLU-66-B1-1R 6th Gen Intel®Core™ Processor i7-6600U Fanless Rugged Embedded System</p> <p>EMS-SKLU-63-B1-1R 6th Gen Intel®Core™ Processor i5-6300U Fanless Rugged Embedded System</p> <p>EMS-SKLU-61-B1-1R 6th Gen Intel®Core™ Processor i3-6100U Fanless Rugged Embedded System</p> <p>EMS-SKLU-39-B1-1R 6th Gen Intel®Celeron Processor 3955U Fanless Rugged Embedded System</p>